

8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF GREENFIELD MFG CO ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF GREENFIELD MFG CO IS PROHIBITED.

HEX NUTS,ZN PLTD	371	ASTM A563 Grade A		1/4 ... 1.0
HVY HEX NUTS	172	ASTM A563 Grade A		1/4 ... 1.0
HVY HEX NUTS,ZN PLTD	372	ASTM A563 Grade A		1/4 ... 1.0
ROD COUPLINGS	151	IFI 128		1/4 ... 1.0
WASHERS	153	ANSI B18.2.1	USS	1/4 ... 1.0
WASHERS,ZN PLTD	353	ANSI B18.2.1	USS	1/4 ... 1.0
BOLTS	156	ASTM A563 Grade A		5/8 AND 3/4
THREADED ROD	900/901	MSS SP-58	LOW CARBON	1/4 ... 1.0
THREAD ROD SIZE		MAX REC LOAD LBS		
3/8 - 16		600		
1/2 - 13		1100		
5/8 - 11		1800		
3/4 - 10		2700		
7/8 - 9		3700		
1 - 8		4900		

***THREAD ROD CONFORMS TO MSS SP-58
LOW CARBON STEEL ALL THREAD ROD
6 FT LENGTHS ONLY***

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		GREENFIELD MFG CO	
TOLERANCES ARE: FRACTIONS DECIMALS ANGLES +/- 1/8 .XX +/- .03 .XX + 1 .XXX +/- .01		APPROVALS	DATE	920 LEVICK ST , PHILA.,PA. 19111	
MATERIAL		DRAWN EG		HARDWARE SPECS	
STEEL		CHECKED SB			
		1/11		A	P/N
DO NOT SCALE DRAWING					REV.
				SCALE	CAD FILE:
					SHEET OF